










1	VISTA ISOMETRICA - ISOMETRIC VIEW - VUE ISOMÉTRIQUE ISOMETRISCHE ANSICHT - VISTA ISOMÉTRICA
2	DIMENSIONALI - DIMENSIONS - DIMENSIONS ABMESSUNGEN - DIMENSIONES
3	PASSAGGIO CAVI - CABLE ENTRY - ENTRÉE CÂBLES KABELDURCHFÜHRUNG - ENTRADA CABLES
4	FISSAGGIO - MOUNTING - MONTAGE BEFESTIGUNG - FIJACIÓN
5	PER EVITARE L'APERTURA IMPROPRIA, BLOCCARE IL PRODOTTO UTILIZZANDO IL COLLARE DI SICUREZZA FORNITO TO AVOID IMPROPER OPENING, LOCK THE PRODUCT USING THE SAFETY COLLAR PROVIDED POUR EVITER L'OUVERTURE IMPROPRE, BLOQUER LE PRODUIT AVEC LA VIS ET LE COLLIER DE SÉCURITÉ FOURNI UM EINE UNANGEMESSENE ÖFFNUNG ZU VERMEIDEN, SPERREN SIE DAS PRODUKT MIT DER SICHERHEITS-KRAGEN (IM LIEFERUMFANG) PARA EVITAR LA APERTURA INDEBIDA, BLOQUEAR EL PRODUCTO CON EL COLLAR DE SEGURIDAD SUMINISTRADO

LT POLE 12÷24V DC/AC 50/60Hz LT POLE PNP 12÷24V DC		MT POLE 40÷80V DC/AC 50/60Hz HT POLE 120÷240V AC 50/60Hz	
1 	1 	2 	3 
4 	4 	4 	5 
5 			

ATTENZIONE	Togliere tensione prima di intervenire sul prodotto
ATTENTION	Disconnect power before servicing
ATTENTION	Débranchez l'alimentation avant de toute intervention sur le produit
ACHTUNG	Schalten Sie die Stromversorgung vor der Wartung
ATENCIÓN	Desconecte la corriente antes de abrir el producto

Per il cablaggio usare cavo per esterno
Wiring with cable for external use
Pour le câblage utiliser cable pour usage externe
Für die Verkabelung is ein Kabel zur äußeren Anwendung zu benutzen
Para el cableado utilizar cable para uso en exteriores


NON SMALTIRE COME RIFIUTO URBANO - NOT TO BE DISPOSED OF AS COMMON WASTE - NE PAS ELIMINER COMME DECHET URBAIN
NICHT ÜBER DIE NORMALE SAMMLUNG VON HAUSMÜLL ENTSORGEN - NO ELIMINAR COMO DESECHO URBANO

- ISTRUZIONI DI INSTALLAZIONE E UTILIZZO - INSTALLATION AND APPLICATION INSTRUCTIONS -
- INSTRUCTIONS D' INSTALLATION ET D' UTILISATION - INSTALLATIONS- UND BEDIENTUNGSANLEITUNG -
- INSTRUCCIONES DE INSTALACIÓN Y EMPLEO -

1	VISTA ISOMETRICA - ISOMETRIC VIEW - VUE ISOMÉTRIQUE ISOMETRISCHE ANSICHT - VISTA ISOMÉTRICA
2	DIMENSIONALI - DIMENSIONS - DIMENSIONS ABMESSUNGEN - DIMENSIONES
3	PASSAGGIO CAVI - CABLE ENTRY - ENTRÉE CÂBLES KABELDURCHFÜHRUNG - ENTRADA CABLES
4	FISSAGGIO - MOUNTING - MONTAGE BEFESTIGUNG - FIJACIÓN
5	PER EVITARE L'APERTURA IMPROPRIA, BLOCCARE IL PRODOTTO UTILIZZANDO LA VITE E LA RONDELLA FORNITE TO AVOID IMPROPER OPENING, LOCK THE PRODUCT USING THE SCREW AND THE WASHER PROVIDED POUR EVITER L'OUVERTURE IMPROPRE, BLOQUER LE PRODUIT AVEC LA VIS ET LA RONDELLE FOURNIES UM EINE UNANGEMESSENE ÖFFNUNG ZU VERMEIDEN, SPERREN SIE DAS PRODUKT MIT DER SCHRAUBE UND DER SCHEIBE (IM LIEFERUMFANG) PARA EVITAR LA APERTURA INDEBIDA, BLOQUEAR EL PRODUCTO CON EL TORNILLO Y LA ARANDELA SUMINISTRADOS




LT SHALLOW 12÷24V DC/AC 50/60Hz




LT DEEP 12÷24V DC/AC 50/60Hz
LT DEEP PNP 12÷24V DC

MT DEEP 40÷80V DC/AC 50/60Hz
HT DEEP 120÷240V AC 50/60Hz



1	VISTA ISOMETRICA - ISOMETRIC VIEW - VUE ISOMÉTRIQUE ISOMETRISCHE ANSICHT - VISTA ISOMÉTRICA
2	DIMENSIONALI - DIMENSIONS - DIMENSIONS ABMESSUNGEN - DIMENSIONES
3	PASSAGGIO CAVI - CABLE ENTRY - ENTRÉE CÂBLES KABELDURCHFÜHRUNG - ENTRADA CABLES
4	FISSAGGIO - MOUNTING - MONTAGE BEFESTIGUNG - FIJACIÓN
5	PER EVITARE L'APERTURA IMPROPRIA, BLOCCARE IL PRODOTTO UTILIZZANDO LA VITE E LA RONDELLA FORNITE TO AVOID IMPROPER OPENING, LOCK THE PRODUCT USING THE SCREW AND THE WASHER PROVIDED POUR EVITER L'OUVERTURE IMPROPRE, BLOQUER LE PRODUIT AVEC LA VIS ET LA RONDELLE FOURNIES UM EINE UNANGEMESSENE ÖFFNUNG ZU VERMEIDEN, SPERREN SIE DAS PRODUKT MIT DER SCHRAUBE UND DER SCHEIBE (IM LIEFERUMFANG) PARA EVITAR LA APERTURA INDEBIDA, BLOQUEAR EL PRODUCTO CON EL TORNILLO Y LA ARANDELA SUMINISTRADOS

LT WALL 12÷24V DC/AC 50/60Hz
LT WALL PNP 12÷24V DC
MT WALL 40÷80V DC/AC 50/60Hz
HT WALL 120÷240V AC 50/60Hz



1	VISTA ISOMETRICA - ISOMETRIC VIEW - VUE ISOMÉTRIQUE ISOMETRISCHE ANSICHT - VISTA ISOMÉTRICA
2	DIMENSIONALI - DIMENSIONS - DIMENSIONS ABMESSUNGEN - DIMENSIONES
3	PASSAGGIO CAVI - CABLE ENTRY - ENTRÉE CÂBLES KABELDURCHFÜHRUNG - ENTRADA CABLES
4	FISSAGGIO - MOUNTING - MONTAGE BEFESTIGUNG - FIJACIÓN
5	PER EVITARE L'APERTURA IMPROPRIA, BLOCCARE IL PRODOTTO UTILIZZANDO LA VITE E LA RONDELLA FORNITE TO AVOID IMPROPER OPENING, LOCK THE PRODUCT USING THE SCREW AND THE WASHER PROVIDED POUR EVITER L'OUVERTURE IMPROPRE, BLOQUER LE PRODUIT AVEC LA VIS ET LA RONDELLE FOURNIES UM EINE UNANGEMESSENE ÖFFNUNG ZU VERMEIDEN, SPERREN SIE DAS PRODUKT MIT DER SCHRAUBE UND DER SCHEIBE (IM LIEFERUMFANG) PARA EVITAR LA APERTURA INDEBIDA, BLOQUEAR EL PRODUCTO CON EL TORNILLO Y LA ARANDELA SUMINISTRADOS

LT DOUBLE 12÷24V DC/AC 50/60Hz
 LT DOUBLE PNP 12÷24V DC
 MT DOUBLE 40÷80V DC/AC 50/60Hz
 HT DOUBLE 120÷240V AC 50/60Hz

1

2

3

4

5