

SIRENA XLINE WIRING BASE

DATASHEET



Base di cablaggio
Wiring base
Base de câblage
Verdrahtungssockel
Base de connexion

CORPO

BODY
CORPS
GEHAUSE
CUERPO DEL PRODUCTO

PC

COLORI DISPONIBILI

AVAILABLE COLOURS
COULEURS DISPONIBLES
VERFÜGBARE FARBEN
COLORES DISPONIBLE



SERVIZIO

OPERATION
FONCTIONNEMENT
BETRIEBSART
FUNCIONAMIENTO

∞

CORRENTE NOMINALE

NOMINAL CURRENT
COURANT NOMINAL
STROMAUFNAHME
CONSUMO DE CORRIENTE

Vac	24	-	110	240
Vdc	-	24	-	-
Wiring Base (mA)	50	40	10	10

TENSIONE DI ALIMENTAZIONE

SUPPLY VOLTAGE
TENSION D'ALIMENTATION
SPANNUNG
TENSÓN

24Vac/dc — 110/240Vac

GRADO IK

IK RATING
DEGRE IK
KLASSE IK
GRADO IK

IK08

TEMPERATURA DI FUNZIONAMENTO

OPERATING TEMPERATURE
TEMPERATURE DE SERVICE
BETRIEBSTEMPERATUR
TEMPERATURA DE FUNCIONAMIENTO

-40°C +60°C

TEMPERATURA DI STOCCAGGIO

STORAGE TEMPERATURE
TEMPERATURE DE STOCKAGE
LAGERTEMPERATUR
TEMPERATURA DE ALMACENAMIENTO

-40°C + 80°C

VIBRAZIONI

VIBRATIONS
VIBRATIONS
VIBRATIONEN
VIBRACIONES

INDUSTRIAL CEI 60068-2-6 SINE

CERTIFICAZIONI, OMOLOGAZIONI

CERTIFICATIONS, APPROVALS
CERTIFICATIONS, HOMOLOGATIONS
PRODUKTZERTIFIKATE, ZULASSUNGEN
CERTIFICADOS, HOMOLOGACIONES

CE, UKCA, RED

FISSAGGIO MOUNTING FIXATION FIXIERUNG FIJACIÓN	Avvitamento Screwing Baise Verschrauben Atornillando
GRADO IP IP RATING DEGRE IP KLASSE IP GRADO IP	IP66 — IP69K

DISEGNO TECHNICAL DRAWING DESSIN TECHNISCHE ZEICHNUNG DIBUJO TECNICO	
---	--